

This page [needs review](#)

Historical overview of Maps integration in Tiki

Maps have been supported in Tiki since 2003 (which is why some call it a GeoCMS). There is geo-related info in various places (users, trackers, image galleries, articles, blog posts, etc.). This was originally done using [MapServer](#), an active and powerful FLOSS mapping solution. However, it requires a dedicated server and more importantly, access to map data (which is not easy).

Later on, [Google Maps](#) arrived, providing an easy to use map integration to regular web sites, even without having to manage mapping data. Thus, Google Maps specific code was added to Tiki, which was convenient for a lot of people.

Then, after [a community discussion](#), starting in [Tiki7](#), [OpenLayers](#) (another option was [Mapstraction](#)) was added as a native way to handle maps, which permits the use of tiles from Google Maps, Bing Maps, OpenStreetMap (which is like Wikipedia but for maps), MapQuest (which serves OpenStreetMap maps), etc.

The [Cartograf](#) project further improved maps in [Tiki8](#), [Tiki9](#), [Tiki10](#) and [Tiki11](#). Many features were added, including Street View support.

In [Tiki12](#), all Google Maps specific code was [removed](#) in favor of using OpenLayers, so Google Maps is accessible via the [OpenLayers Google Layer](#). In addition the Natural Access project (no longer active) added further new capabilities to upload any existing line and polygon data as files and to be able to further customise how data objects were shown on the underlying map layer.

In [Tiki15](#) all MapServer-specific code has been removed. Also OpenLayers 2.x continues to be used for the map layer and integration with Tiki to allow editable map objects to be overlaid on the map layer but experimentation has started with the integration of OpenLayers 3.x.

In [Tiki20](#) integration with OpenLayers 3.x and higher was improved, and more features were exposed through the corresponding [PluginMap](#) parameters, as well as adding new tilesets, some of them using vector tiles instead of just the usual raster tiles.

Map-related documentation, as of summer of 2019, still makes reference to the different historical approaches but as it continues to be improved the older methods that are no longer used will be deprecated/removed. Volunteers to help with documentation improvement : please contact marclaporte at tiki dot org

See [PluginGoogleMap](#), which is bundled in Tiki5

Information on this page is outdated starting from Tiki5. The mod below is no longer supported as it has been replaced by [PluginGoogleMap](#) which is bundled in Tiki 5

Mod Gmap

This is a [Wiki plugin](#), distributed as a [mod](#) for displaying a [Gmap](#) in a wiki page, where each page represents a marker on a global map. The mod creates a geo-coded location of a wiki page, backlinked pages, or pages in a structure. It is currently available only as a [mod](#), which means you have to upload the files to replace the current gmap plugin.

Author: Nelson Ko

License: LGPL

Last Version: 1.0 (2007-06-30)

Download: mods.tiki.org or use mods in your tikiwiki to install.

Note: be sure to turn on feature googlemaps and get them working first including the google activation code.

Plugin Syntax:

```
{GMAP(type=>page, width=>400, controller=>none, mode=>normal)/}
```

- optional parameters are separated by commas
- there are no spaces anywhere, except after commas.

Parameters

| Parameter | Accepted values | Description | Default |
|------------|-----------------|---|---------|
| type | page | maps the current single page | page |
| | backlinks | maps the backlinks of the current page | |
| | structure | maps the pages in the structure that the current page is in | |
| | route | maps the pages in the structure that the current page is in and draws a line between points as in a route | |
| width | number | width in pixels | 500 |
| height | number | height in pixels | 400 |
| controller | large | this contains pan/zoom buttons and clickable zoom scale | large |
| | medium | this contains pan/zoom buttons but no clickable zoom scale | |
| | small | this contains zoom buttons only | |
| | none | the controller is disabled | |
| changetype | y/n | the buttons to change the mode of the map can be disabled | y |
| scale | y/n | the display of the map scale can be disabled | y |
| mode | normal | start the map in normal streetmap mode | normal |
| | satellite | start the map in satellite mode | |
| | hybrid | start the map in satellite/streetmap hybrid mode | |

Notes:

- To use this plugin, you should set the cache time for wiki pages = 0 (no caching), otherwise you may have difficulties editing geolocations (or seeing the edits you have made anyway). Set the wiki cache in Admin>Wiki
- Having multiple google maps on the same page is not recommended as it can cause unpredictable results.

Using this Plugin

Type=Page

The default syntax (above), when saved in a wiki page will produce the following map.

map and geotagging for this page not yet saved 



At this point you can:

- click on the + sign to open the location editor.
- type in an address and "GO" to that address.
- single click on the map directly to create a point on the current map.

Using the Location Editor

map and geotagging for this page not yet saved 

Once you have created a point on the map, you can edit the information that appears in the balloon. The latitude and longitude information is normally not editable. You change the location by clicking on the map or by searching to a new address.

- [Wiki Plugin](#)
- [Mods Type Wikiplugins](#)

Requirements and additional instructions: This plugging may be added via the mods admin panel at `yourdomain.com/tiki-mods.php`. These steps below should be taken care of through the mods deployment process. Otherwise the manual steps required are:

1. This file is to be deployed to `<tikiroot>/lib/wiki-plugins/`
2. Included `gmapwikipluginlib.php` should be deployed to `<tikiroot>/lib/wiki-plugins/`
3. Included `gmap_wikiplugin_save.php` should be deployed to `<tikiroot>/`
4. The following included smarty templates should be deployed to `<tikiroot>/templates/wiki-plugins/`: `wikiplugin-backlinkgmap.tpl`, `wikiplugin-gmap.tpl`, `wikiplugin-routegmap.tpl`, `wikiplugin-structuregmap.tpl`
5. The following SQL command is to be executed to create the necessary database table: `CREATE TABLE `wikiplugin_gmap` (`pageid` int(14) NOT NULL, `pref` varchar(40) NOT NULL, `value` varchar(250) default NULL, PRIMARY KEY (`pageid`,`pref`)) TYPE=MyISAM;`
6. In order for route type to work and for the google maps polylines to work, the VML namespace must be specified in the html tag in `<tikiroot>/templates/header.tpl`, like this: `<html xmlns="http://www.w3.org/1999/xhtml" xmlns:v="urn:schemas-microsoft-com:vml">`
7. When using the plugin, click on the "+" icon next to the text at the top to access the geocoding information. The coordinates are automatically into the fields there through mouse clicks on the map.
8. Note that having multiple google maps on the same page is not recommended as it can cause unpredictable results.