

# Plugin Twitter

Introduced in [Tiki7](#)

Use this [wiki plugin](#) to display the activity for a Twitter account.

## Parameters

Display the activity for a twitter account

Introduced in [Tiki 7](#). Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_twitter`

Parameters	Accepted Values	Description	Default	Since
<b>tweet</b>	text	Depends on the type of timeline (Users, Collections, Favorites or Lists). For a User, it is the Account Name (like <code>twitterdev</code> ), for Favorites, something like <code>twitterdev/favorites</code> . For lists, something like <code>twitterdev/lists/listname</code> , etc.		7.0
<b>widgetId</b>	digits	Numeric identifier of the widget		13.1
<b>tweetbg</b>		Change the border color used by the widget. Default is theme default.		7.0
<b>height</b>	digits	Height of widget in pixels. Default is 300.	300	7.0
<b>tweetcolor</b>		Text color for individual tweets. Default is theme default.		7.0
<b>noborders</b>	(blank) y	Default is with Borders		13.1
<b>nofooter</b>	(blank) y	Default is with Footer		13.1
<b>noheader</b>	(blank) y	Default is with Header		13.1
<b>noscrollbar</b>	(blank) y	Default is with Scrollbar		13.1
<b>theme</b>	(blank) light dark	Embedded timelines are available in light and dark themes for customization. The light theme is for pages that use a light colored background, while the dark theme is for pages that use a dark colored background. Default is <code>light</code> .	light	13.1
<b>shellbg</b>	(blank) transparent	Transparent Shell Background. Default is theme default		7.0
<b>width</b>		Width of widget in pixels or 'auto' to fit to width of page. Default is <code>auto</code> .	auto	7.0

Note that Twitter requires that you have an account on Twitter and that you first create your widget there, so you get a `widgetId` number from Twitter for the widget

# Example

## Basic syntax

```
{twitter tweet="tikiwiki" widgetId="xxxxxxxx" }
```