

# General Preferences tab

## Overview

Configure site-wide preferences

## To Access

From the General Admin page, click the **General Preferences** tab.

## Note

Some of these options can be configured during Installation

### Related Topics

- [Installation](#)
- [System Log](#)
- [Look and Feel](#)

To see all the settings available on your admin page, you may need to adjust your Preference Filters

Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	

Option	Description	Default
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun Region		
Mandrill Key		
Postmark Key		
SendGrid Key		
SendGrid Region		
SparkPost Key		
SparkPost Region		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	

Option	Description	Default
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
Reset password token expiry time	Time in minutes before a reset password link expires.	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the tiki_sql_query_logs table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log failed logins	Failed logins will be logged with respective login error code.	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	

Option	Description	Default
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Allow shell command execution	Give the possibility to execute shell commands.	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled.Ex: <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed.Ex: <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	
Minutes hold warning message	Minutes to hold admin warning message when scheduler was not executed recently, set 0 (zero) to not display the message.	
Headless Browser Integration Type	Type of headless browser integration to be used.	
Chrome Binary Path	This ensures that the ChromePHP library can locate and execute the Chrome browser for headless operations	
Display maintenance message to users during search re-index	If enabled, a message will be displayed to users during search re-index.	
Search re-index message	The message displayed during search re-indexing. You can customize this message if needed.	

Option	Description	Default
Time before maintenance to display the message (minutes)	The time will be used for display warning message before start maintenance.	
Recurrent Maintaine Enabled	Enable notification during maintenance.	
Before Maintenance Message	Message to display before maintenance starts. Use TIME for minutes until maintenance and DOWN for duration.	
During Maintenance Message	Message to display during maintenance. Use DOWN for remaining minutes of downtime.	
Start Time	It is for set when the maintenance will be started (24H format hh:mm)	
Duration (Minutes)	Period to display message while maintenance.	
Enable notifitication during maintenance on weekdays		
Once off notifikation maintenance enabled	Enable notifitication once off maintenance.	
Before Once-Off Maintenance Message	Message to display before once-off maintenance starts. Use TIME for minutes until maintenance and DOWN for duration.	
During Once-Off Maintenance Message	Message to display during once-off maintenance. Use DOWN for remaining minutes of downtime.	
Start Date	It is for set date the maintenance will be off	
Start Time	It is for set when the maintenance will be off (24H format hh:mm)	
Duration (Minutes)	Period to display message while maintenance once off.	
Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	

Option	Description	Default
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		

Option	Description	Default
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the tiki_sql_query_logs table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log failed logins	Failed logins will be logged with respective login error code.	

Option	Description	Default
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Allow shell command execution	Give the possibility to execute shell commands.	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled.Ex: <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed.Ex: <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	
Minutes hold warning message	Minutes to hold admin warning message when scheduler was not executed recently, set 0 (zero) to not display the message.	
Headless Browser Integration Type	Type of headless browser integration to be used.	
Chrome Binary Path	This ensures that the ChromePHP library can locate and execute the Chrome browser for headless operations	



Option	Description	Default
Display maintenance message to users during search re-index	If enabled, a message will be displayed to users during search re-index.	
Search re-index message	The message displayed during search re-indexing. You can customize this message if needed.	
Time before maintenance to display the message (minutes)	The time will be used for display warning message before start maintenance.	
Recurrent Maintaine Enabled	Enable notification during maintenance.	
Before Maintenance Message	Message to display before maintenance starts. Use TIME for minutes until maintenance and DOWN for duration.	
During Maintenance Message	Message to display during maintenance. Use DOWN for remaining minutes of downtime.	
Start Time	It is for set when the maintenance will be started (24H format hh:mm)	
Duration (Minutes)	Period to display message while maintenance.	
Enable notifitication during maintenance on weekdays		
Once off notification maintenance enabled	Enable notifitication once off maintenance.	
Before Once-Off Maintenance Message	Message to display before once-off maintenance starts. Use TIME for minutes until maintenance and DOWN for duration.	
During Once-Off Maintenance Message	Message to display during once-off maintenance. Use DOWN for remaining minutes of downtime.	
Start Date	It is for set date the maintenance will be off	
Start Time	It is for set when the maintenance will be off (24H format hh:mm)	
Duration (Minutes)	Period to display message while maintenance once off.	
Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and require database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	

Option	Description	Default
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		

Option	Description	Default
Port		25
Security		SSL
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	no
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	localhost
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	Queue
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	catchall@localhost
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	10
Newsletter pause length	Number of seconds delay before each batch	10
Newsletter batch size	Number of emails to send in each batch	100
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	no
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	0
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	no
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	no
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	no
Generic error message	Message to display to non admin users when an error occurs.	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	no

Option	Description	Default
Log SQL	All SQL queries will be registered in the database in the tiki_sql_query_logs table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Allow shell command execution	Give the possibility to execute shell commands.	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled.Ex: admin,operations@example.com <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed.Ex: admin,operations@example.com <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	
Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and requite database or shell access to recover it.</i>	

Option	Description	Default
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		

Option	Description	Default
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	

Option	Description	Default
Generic error message	Message to display to non admin users when an error occurs.	
Disable JavaScript	Disable JavaScript for the purpose of testing even if enabled in the browser. <i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i>	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the adodb_logsqli table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. <b>Ex:</b> <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. <b>Ex:</b> <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Server domain name	The value that will be used by default as the server domain name of your Tiki site. <i>Leave this blank if you are not entirely sure what you are doing. If this value is incorrect or your DNS is not set up properly it will lock you out of your Tiki and requite database or shell access to recover it.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: https://example.com/tiki/), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at ./temp/Mail_yyyymmddhhmmss_randomstring.tmp ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		
Mandrill Key		
Postage Key		
Postmark Key		



Option	Description	Default
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery. Only works with SMTP mail.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	

Option	Description	Default
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Show generic error message	Show a generic error message for non admins users. The error is logged to the database.	
Generic error message	Message to display to non admin users when an error occurs.	
Disable JavaScript	Disable JavaScript for the purpose of testing even if enabled in the browser. <i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i>	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the adodb_logsql table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Sample rate	Sampling allows you to better manage the number of reported events, so you can tailor the volume of data needed. Use a value between 0 and 1. E.g.: 0.25 (will report 25% of the events)	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. <b>Ex:</b> <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	

Option	Description	Default
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. Ex: <code>admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: <code>https://example.com/tiki/</code> ), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at <code>./temp/Mail_yyyymmddhhmmss_randomstring.tmp</code> ) to send mail notifications.	
Amazon SES Key		
Amazon SES Secret		
Amazon SES Region		
Amazon SES version		
Elastic Email Username		
Elastic Email Key		
Mailgun Domain		
Mailgun Key		
Mailgun API Endpoint		

Option	Description	Default
Mandrill Key		
Postage Key		
Postmark Key		
SendGrid Username		
SendGrid Key		
SparkPost Key		
SMTP server		
Authentication	Mail server authentication	
Username		
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery. Only works with SMTP mail.	
Catch-all email address	Tiki will send all emails to this email address instead of the target recipients. This will actually rewrite the recipient TO, CC and BCC email headers.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	

Option	Description	Default
PHP errors visible to admin only	<p>PHP Errors will be shown to only the Admin user.</p> <p><i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i></p>	
Include Smarty notices in the PHP error report	<p>Tiki will display Smarty notices with the PHP error messages.</p> <p><i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i></p>	
Disable JavaScript	<p>Disable JavaScript for the purpose of testing even if enabled in the browser.</p> <p><i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i></p>	
Log mail in Tiki logs	<p>A line of type mail will be included in the System Log with the destination address and subject of each email sent.</p> <p><i>May impact performance</i></p>	
Log SQL	<p>All SQL queries will be registered in the database in the adodb_logsqli table.</p> <p><i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i></p>	
Log queries using more than	<p>Use to log only queries that exceed a specific amount of time.</p> <p><i>May impact performance</i></p>	
Data Source Name (DSN)	DSN used for connect to the error tracking service.	
Track PHP errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for PHP.	
Track JavaScript errors	Enable integration with error tracking service(ex: Sentry, GlitchTip) for JavaScript.	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Delay scheduled time (minutes)	When calculating if the jobs should run, take the delay into consideration	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	<p>List of users/emails separated by comma to be notified when a scheduler task is set to stalled.<b>Ex:</b></p> <p><code>admin,operations@example.com</code><b>If empty, the email will be sent to all administrators.</b></p>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	

Option	Description	Default
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. <code>Ex: admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	

Option	Description	Default
Upgrade cycle	Tiki upgrade frequency for this site to check against.	
Check for updates automatically	Tiki will automatically check for new updates each time you access the Admin Home page, based on your Check frequency selection. <i>Subscribe to the Tiki Newsletter to be notified of new releases. <a href="https://doc.tiki.org/Newsletters">https://doc.tiki.org/Newsletters</a></i>	
Check frequency	How often Tiki should check for updates. This field applies only if "Check for updates automatically" is enabled. <i>Click "Check for Updates Now" to perform an update check.</i>	
Browser title	Visible label in the browser's title bar on all pages. Also appears in search engine results.	
Server domain name	The value that will be used by default as the server domain name of your Tiki site.	
Fallback for tiki base URL	The full URL to the Tiki base URL including protocol, domain and path (example: <a href="https://example.com/tiki/">https://example.com/tiki/</a> ), used when the current URL can not be determined, example, when executing from the command line.	
Browser title position	Position of the browser title in the full browser bar relative to the current page's descriptor.	
Browser title display mode	When breadcrumbs are used, method to display the browser title.	
Sender email	Email address that will be used as the sender for outgoing emails.	
Sender full name	Real name that will be used as the sender for outgoing emails	
Default character set for sending mail	Specify the character encoding used by Tiki when sending mail notifications.	
Email newline character(s)	End-of-line (EOL) character used in outgoing emails	
Apply site styles to HTML emails	Add site CSS to all HTML formatted emails	
Mail sender	Specify if Tiki should use Sendmail(the PHP mail() function), SMTP or File (Debug) (to debug email sending by means of storing emails as files on disk at <code>./temp/Mail_yyyymmddhhmmss_randomstring.tmp</code> ) to send mail notifications.	
SMTP server		
Authentication	Mail server authentication	
Username		

Option	Description	Default
Password		
Port		
Security		
Verify HTTPS certificates of remote servers	When set to enforce, the server will fail to connect over HTTPS to a remote server that do not have a SSL certificate that is valid and can be verified against the local list of Certificate Authority (CA)	
Local server name	Name of the local server. Will be reported to SMTP relay on the HELO/EHLO line.	
Mail delivery	When set to Queue, messages will be stored in the database. Requires using the shell script <code>php console.php mail-queue:send</code> to be run for actual delivery. Only works with SMTP mail.	
Email footer	Text appended to outgoing emails.	
Text string used to customise mail templates	Text string used to customise mail templates and added as a pref reference in the appropriate mail tpl files	
Throttle newsletter send rate	Pause for a given amount of seconds before each batch to avoid overloading the mail server.	
Newsletter pause length	Number of seconds delay before each batch	
Newsletter batch size	Number of emails to send in each batch	
Allow sending newsletters through external clients	Generate mailto links using the recipients as the BCC list. <i>This will expose the list if email addresses to all users allowed to send newsletters.</i>	
PHP Error reporting level	Level of errors to be reported. Errors can be seen in a collapsible box at the bottom of the page, if any exist.	
PHP errors visible to admin only	PHP Errors will be shown to only the Admin user. <i>During site development, it's better to display errors to all users. However, in production settings, errors should only be displayed to administrators.</i>	
Include Smarty notices in the PHP error report	Tiki will display Smarty notices with the PHP error messages. <i>In most cases, Smarty notices can be safely ignored. However, they may be useful in the development process when unexpected issues occur.</i>	
Disable JavaScript	Disable JavaScript for the purpose of testing even if enabled in the browser. <i>Use only for testing or troubleshooting. When enabled, many Tiki features will not operate correctly.</i>	
Log mail in Tiki logs	A line of type mail will be included in the System Log with the destination address and subject of each email sent. <i>May impact performance</i>	
Log SQL	All SQL queries will be registered in the database in the adodb_logsqli table. <i>Do not enable this feature all the time. It can be very resource intensive and will impact performance.</i>	

Option	Description	Default
Log queries using more than	Use to log only queries that exceed a specific amount of time. <i>May impact performance</i>	
Enabled	Cron jobs can be triggered from a URL or with JavaScript. A token is required to run the cron job manually.	
How to trigger Web Cron		
Run interval	The amount of time of each run	
Token	The token to use when running the cron manually	
Scheduler	Provides the ability to run tasks at a scheduled time.	
Scheduler stalled after (minutes)	Set a scheduler to stall if the running time is long. Set 0 to disable stall detection.	
Notify on stalled schedulers	Send an email notification when a stalled scheduler is detected.	
Users to notify on stalled task	List of users/emails separated by comma to be notified when a scheduler task is set to stalled. <code>Ex: admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Self healing after (minutes)	Self healing resets a stalled scheduler automatically after the timeout set. 0 disables self healing	
Notify on healed schedulers	Send an email notification when a stalled scheduler is healed.	
Users to notify on healed task	List of users/emails separated by comma to be notified when a scheduler task is set to healed. <code>Ex: admin,operations@example.com</code> <b>If empty, the email will be sent to all administrators.</b>	
Number of logs to keep	0 will keep all logs	

related

SMTP