

Security Site Access tab

Overview

Use this tab to configure how Tiki handles the security relating to site access.

To Access

From the Security Admin page, click the **Site Access** tab.

Related Topics

- security admin

| Option | Description | Default |
|--|---|-------------------------------|
| Close site | Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site. | Disabled |
| Title | | Coming soon |
| Message | | Site is closed for maintena.. |
| Close site when server load is above the threshold | Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site. | Disabled |
| Maximum average server load threshold in the last minute | | 3 |
| Site Busy Title | | Server too busy |
| Site Busy Message | | Server is currently too bus.. |
| Enable intrusion detection system | An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations. | Disabled |
| Custom rules file | | temp/ids_custom_rules.json |
| Intrusion detection system mode | Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests | Log only |

| Option | Description | Default |
|--------------------------------------|---|----------|
| Intrusion detection system threshold | Define IDS threshold, when configured in "Log and block requests" more. | 0 |
| Log to file | | ids.log |
| Log to database | | Disabled |

| Option | Description | Default |
|--|---|-------------------------------|
| Close site | Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site. | Disabled |
| Title | | Coming soon |
| Message | | Site is closed for maintena.. |
| Close site when server load is above the threshold | Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site. | Disabled |
| Maximum average server load threshold in the last minute | | 3 |
| Site Busy Title | | Server too busy |
| Site Busy Message | | Server is currently too bus.. |
| Enable intrusion detection system | An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations. | Disabled |
| Custom rules file | | temp/ids_custom_rules.json |
| Intrusion detection system mode | Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests | Log only |
| Intrusion detection system threshold | Define IDS threshold, when configured in "Log and block requests" more. | 0 |
| Log to file | | ids.log |
| Log to database | | Disabled |

| Option | Description | Default |
|--|---|--------------------------------|
| Close site | Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site. | Disabled |
| Title | | Coming soon |
| Message | | Site is closed for maintena... |
| Close site when server load is above the threshold | Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site. | Disabled |
| Maximum average server load threshold in the last minute | | 3 |
| Site Busy Title | | Server too busy |
| Site Busy Message | | Server is currently too bus... |
| Enable intrusion detection system | An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations. | Disabled |
| Custom rules file | | temp/ids_custom_rules.json |
| Intrusion detection system mode | Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests | Log only |
| Intrusion detection system threshold | Define IDS threshold, when configured in "Log and block requests" more. | 0 |
| Log to file | | ids.log |
| Log to database | | Disabled |
| Option | Description | Default |
| Close site | Use this setting to "close" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site. | Disabled |
| Title | | Coming soon |

| Option | Description | Default |
|--|---|-------------------------------|
| Message | | Site is closed for maintena.. |
| Close site when server load is above the threshold | Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site. | Disabled |
| Maximum average server load threshold in the last minute | | 3 |
| Site Busy Title | | Server too busy |
| Site Busy Message | | Server is currently too bus.. |
| Enable intrusion detection system | An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations. | Disabled |
| Custom rules file | | temp/ids_custom_rules.json |
| Intrusion detection system mode | Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests | Log only |
| Intrusion detection system threshold | Define IDS threshold, when configured in "Log and block requests" more. | 0 |
| Log to file | | ids.log |
| Log to database | | Disabled |

| Option | Description | Default |
|--|---|-------------------------------|
| Close site | Use this setting to \"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site. | Disabled |
| Title | | Coming soon |
| Message | | Site is closed for maintena.. |
| Close site when server load is above the threshold | Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site. | Disabled |

| Option | Description | Default |
|--|---|-------------------------------|
| Maximum average server load threshold in the last minute | | 3 |
| Site Busy Title | | Server too busy |
| Site Busy Message | | Server is currently too busy. |
| Enable intrusion detection system | An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations. | Disabled |
| Custom rules file | | temp/ids_custom_rules.json |
| Intrusion detection system mode | Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests | Log only |
| Intrusion detection system threshold | Define IDS threshold, when configured in "Log and block requests" more. | 0 |
| Log to file | | ids.log |
| Log to database | | Disabled |

| Option | Description | Default |
|--|---|-------------------------------|
| Close site | Use this setting to \"close\" the Tiki site (such as for maintenance). Users attempting to access the site will see only a log-in form. Only users with specific permission will be allowed to log in. Use the Message to display to specify the message that visitors will see when attempting to access your site. | Disabled |
| Title | | Coming soon |
| Message | | Site is closed for maintena.. |
| Close site when server load is above the threshold | Use this option to "close" the Tiki site when the server load exceeds a specific threshold. Only users with specific permission will be allowed to log in. Use "Maximum average server load threshold in the last minute" to define the maximum server load. Use the "Message to display" to specify the message that visitors will see when attempting to access the site. | Disabled |
| Maximum average server load threshold in the last minute | | 3 |
| Site Busy Title | | Server too busy |
| Site Busy Message | | Server is currently too bus.. |

| Option | Description | Default |
|--------------------------------------|---|----------------------------|
| Enable intrusion detection system | An intrusion detection system (IDS) is a device or software application that monitors a network or systems for malicious activity or policy violations. | Disabled |
| Custom rules file | | temp/ids_custom_rules.json |
| Intrusion detection system mode | Define IDS operation mode, log only, or log and block with impact over a given threshold. ☰ Log only Log and block requests | Log only |
| Intrusion detection system threshold | Define IDS threshold, when configured in "Log and block requests" more. | 0 |
| Log to file | | ids.log |
| Log to database | | Disabled |

Close site

Activated with the "Close site when server load is above the threshold" or "Close Site" preferences. The site will be closed but allow groups with *tiki_p_access_closed_site* permission to log in.

The page displayed when the site is closed is generated from a template HTML file called *templates/styles/site_closed.html*. If you want to customise this, it is recommended you make a copy of it called *site_closed_local.html* and edit that. This will be used in preference to the standard one if found.

The following "tags" will be replaced in the HTML:

{title}

Page title and H1 tags

{error}

Text displayed under the title heading

{login}

The login form

{back}

A browser back button (probably will be removed because this doesn't always make sense)

Alias: Site Closed
Alias: Close Site