Cron Job to Rebuild Search Index

You can rebuild index by visiting example.com/tiki-admin.php?page=search&rebuild=now

Since Tiki9, if you have a large site and do not use MySQL Full Text search, you should set up a Cron job to regularly rebuild the index.

How to do it varies from server to server, but here is an example. For a fuller description of the commands themselves, please see Unified Index - from the command line

Add this line for a daily rebuild in Tiki11 and up

0 0 * * * cd /var/www/html/tiki; php console.php index:rebuild >/dev/null 2>&1

To set RAM to 4 GB, increase max execution time, force an initial index cleanup and log

 $0\ 0\ *** cd /var/www/html/tiki; php -dmemory_limit=4G -dmax_execution_time=300\ console.php\ index:rebuild --force --log >/dev/null\ 2>\&1$

Works in Shell but not as a Cron Job

The environment for a cron job (e.g., the PATH variable) may not be the same as in shell (using SSL can cause this). That means that the above scripts may work in shell but not as a cron job. To solve this, set the cron job to run a shell script that sets the PATH variable before running the rebuild command.

To find out what the PATH variable should be, use the env command in shell on the server where the Tiki site is that you're rebuilding the index for.

Let's say the shell script is called cron.sh. The cron job would be as follows:

Cron job to run shell script

0 0 * * * sh cron.sh >/dev/null 2>&1

The shell script cron.sh would consist of the following:

cron.sh

 $\#!/\mbox{bin/bash}$ $\#\mbox{this}$ is the exact same setting as in the shell environment

PATH=/home/useraccount/perl5/bin:/usr/local/bin:/usr/local/sbin:/usr/sbin:/usr/sbin:/home/useraccount/bin #this is the actual command to rebuild the index php -dmemory_limit=4G -dmax_execution_time=300 /home/useraccount/public html/console.php index:rebuild

Related:

- Batch
- Cron
- Search
- Search and List from Unified Index

•	Scheduler
alias	
•	Cron Job for Search