

# Plugin Mouseover

Introduced in [Tiki3](#)

Use this [wiki plugin](#) to display hidden content by mousing over text.

## Parameters

Display hidden content by mousing over text

Introduced in Tiki 3. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: `wikiplugin_mouseover`

Parameters	Accepted Values	Description	Default	Since
(body of plugin)		Hidden content, unless the <code>label</code> parameter is undefined, in which case this is the label.		
<b>label</b>	text	Text displayed on the page. The body is the hidden content.	3.0	
<b>url</b>	url	Destination link when mouseover text is clicked. Use <code>http://</code> for external links	<code>javascript:void(0)</code>	3.0
<b>bgcolor</b>	text	Background color to apply to the popup		3.0
<b>class</b>	text	CSS class to apply	<code>plugin-mouseover</code>	4.0
<b>closeDelay</b>	digits	Number of seconds before popup closes	0	5.0
<b>effect</b>	(blank)  none  slide  fade  blind_ui  clip_ui  drop_ui  explode_ui  fold_ui  puff_ui  slide_ui	Set the type of show/hide animation that will be used		4.0
<b>height</b>	digits	Mouseover box height. Default: <code>200px</code>	200	3.0
<b>offsetx</b>	int	Shifts the overlay to the right by the specified number of pixels relative to the cursor. Default: 5	5	3.0
<b>offsety</b>	int	Shifts the overlay lower by the specified number of pixels relative to the cursor. Default: 0	24	3.0

<code>padding</code>	<code>digits</code>	Padding size in pixels		3.0
<code>tag</code>	<code>word</code>	HTML tag to use for the label. Default <code>a</code>	<code>a</code>	9.2
<code>text</code>	<code>text</code>	DEPRECATED Hidden content. The body contains the label.		3.0
<code>textcolor</code>	<code>text</code>	Color to apply to the text in the popup		3.0
<code>width</code>	<code>digits</code>	Mouseover box width. Default: <code>400px</code>	400	3.0
<code>speed</code>	(blank) fast slow	Set the speed of the animation.		4.0
<code>parse</code>	(blank) y n	Parse the body of the plugin as wiki content (parsed by default)	y	3.0
<code>parselabel</code>	(blank) y n	Parse the label as wiki content (parsed by default)	y	5.0
<code>sticky</code>	(blank) y n	When enabled, popup stays visible until it is clicked.		3.0

## Examples

## Non-sticky Mouseover

*This code:*

```
{MOUSEOVER(label="Hello" offsetx="4" offsety="15")}{Hello over there. It's fine!}{MOUSEOVER}
```

*Would produce:*

Hello

## Sticky Mouseover with Tiki Syntax

*This code:*

```
{MOUSEOVER(label="Sticky" sticky="y" parse="y" offsetx="4" offsety="15")}{This is a "sticky" popup}{MOUSEOVER}
```

*Would produce:*

Sticky