

Plugin Tracker Prefill

Introduced in [Tiki2](#)

Use this [wiki plugin](#) for [trackers](#) to display a button with a link to a page containing a tracker plugin [PluginTracker](#). In the parameters, you will be able to specify default values for some fields.

Parameters

Create a button to prefill tracker fields

Introduced in Tiki 2. Required parameters are in **bold**.

[Go to the source code](#)

Preferences required: feature_trackers, wikiplugin_trackerprefill

Parameters	Accepted Values	Description	Default	Since
value1	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
field1	digits	Field ID for the first field		2.0
page	pagename	Tracker page name		2.0
label	text	Button Label.		2.0
urlparams	any string except for HTML and PHP tags	Parameters to pass in the URL, for example, &my_parameter1=123&my_parameter2=q		6.0
value2	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
value3	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
value4	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
value5	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
value6	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0
value7	any string except for HTML and PHP tags	Content that should be used to prefill the field.		2.0

value8	any string except for HTML and PHP tags	Content that should be used to prefill the field.	2.0
field2	digits	Field ID for the second field	2.0
field3	digits	Field ID for the third field	2.0
field4	digits	Field ID for the fourth field	2.0
field5	digits	Field ID for the fifth field	2.0
field6	digits	Field ID for the sixth field	2.0
field7	digits	Field ID for the seventh field	2.0
field8	digits	Field ID for the eighth field	2.0

Example

```
{trackerprefill page="Order" label="Order" field1="2" value1="Shoes" field2="3" value2="10"}
```

The above syntax will create a button labelled "Order" that will link to `tiki-index_raw.php?page=Order&prefills=2:3&values[]=Shoes&values[]=10`

If the wiki page named "Order" contains a tracker plugin with 2 fields (2 and 3), the tracker form will prefill in the fields 2 and 3 values "Shoes" and "10".